

**SIEMENS**

SIEMENS SMART LOCK - E327

Innovative  
living begins  
today



# SIEMENS

Champagne Gold

Space Grey

Bronze Gold



Siemens Smart Lock

# E327 Features

## SECURITY

### Dual MCU

- Double protection with Individual MCU for internal & external circuits.



### NFC Card with Strong Encryption

- CPU Embedded Card with smart & secure coding.
- Optional Anti-Cloning Access Cards.




### Semiconductor Fingerprint Sensor

- Fingerprint Sensor with wide sensing area, tailor-made by FPC Company.
- High-Security Algorithm with gun safe level encryption.



### Tamper Proof Fingerprint Sensor

- Sensor with protocols against false signals.
- Advanced design against cracking.



### C-Class Cylinder

- C-Class Anti-Drilling Cylinder.
- Key with Double-S shaped grooves.



### Fake PIN Codes

- Up to 20-Digit PIN with redundant digits to foil peaking.
- Fingerprint Residue Resistant Touchpad.



### Child Lock

- 2-Step Unlocking. (Press button while pulling lever).
- Peep Hole tool to prevent intrusion.



## HUMANITY

### Ambient LED Backlighting

- Backlit logo embedded in laser engraved glass.
- Provides a welcoming feel.



### Multiple Unlock Methods

- Fingerprint, PIN Code, Encrypted ID Card & Key.



### Status Alarm

- Abnormal Status & Tamper Alarm.
- Low Battery & Multiple Entry Failure Alert.



### Door Bell

- Integrated Door Bell function.
- Excellent speaker chamber design.



### Voice Menu

- Support for Mandarin, English and Cantonese real human voice dubbling



### Emergency Power Supply

- Concealed USB Type-C Connector.
- Temporary Power Supply Reserves.



### Thumb-Turn Deadbolt

- 2-Step Double Lock (Press down & turn).
- Prevents accidental locking from inside.



Access Solution	Fingerprint / PIN Code / Encrypted ID Card / Key						
Fingerprint Identification	Semiconductor Sensor						
Fingerprint Capacity	Up to 100	Pin Capacity	Up to 50	Pin Length	6 - 12 Digits	Card Capacity	Up to 10
Power Supply	AA Battery x 8, Type-C Charging for Emergency						
Low Battery Indicator	Voice Alert Triggered when voltage is less than 4.8V						
Safety Alert Function	Trigger Alarm after 3 Continuous Authorization Failures, System Disable for 90 Seconds after 5 Failures						
Main Material	Aluminium Alloy						
Product Size (mm)	392 x 79 x 28.5 (Lever Not Include)						
Supported Door Types	Fire Door / Solid Wooden / Timber Door / Burglarproof Metal Door						
Supported Door Thickness	40 - 100mm						
In The Box	Exterior Body, Interior Body, Mortise, AA Batteries x 8, Cylinder, Installation Template, User Manual, Accessories, Keys x 2, Cards x 2						

